

Product guide: Contempo Black Basalt

- Appearance:** In all natural stone there will be variations in colour tones, shades and natural markings and they can display blemishes, veining and minor chips. These are natural characteristics and enhance the uniqueness of the product. We always recommend viewing the product before making a decision. You can do this at our indoor and outdoor show areas. We can supply full size samples for an additional cost to help give an impression of how your finished project will look.
- We regret that we cannot refund or exchange products, once they have been installed, on the basis of texture, colour variation or other natural occurring characteristics.
- Sealing and treating:** Using a sealant on Contempo Black Basalt can help to reduce staining and protect the stone. You can apply this yourself or Kebur can pre-seal your stone for you for an additional cost.
- Installation:** We recommend that all natural stone is laid on a full mortar bed with a suitable sub-base, taking into account the ground conditions and planned usage. For Contempo Black Basalt we recommend substituting ordinary Portland cement with white cement. It should also have an SBR bond slurry mix or similar applied to the underside of the slab to help with adhering to the mortar. Lay Contempo Black Basalt with the textured face upwards.
- Contempo Black Basalt should not be butt jointed. We recommend a minimum joint width of 5mm.
- There may be colour variations between batches of slabs. If laying from more than one pallet, mix slabs to ensure a consistent look.
- Maintenance:** We offer a range of sealers and cleaners you can use yourself. Always read the label and seek professional guidance.

If you have any further questions about installing or caring for Contempo Black Basalt please contact one of our sales advisors who will be very happy to help you.