

Product guide: Contempo Sinai Pearl Limestone

- Appearance:** In all natural stone there will be variations in colour tones, shades and natural markings and they can display blemishes, veining and minor chips. These are natural characteristics and enhance the uniqueness of the product. We always recommend viewing the product before making a decision. You can do this at our indoor and outdoor show areas. We can supply full size samples for an additional cost to help give an impression of how your finished project will look. We regret that we cannot refund or exchange products, once they have been installed, on the basis of texture, colour variation or other natural occurring characteristics.
- Colour:** Contempo Sinai Pearl Limestone will fade slightly after being exposed to the British weather over a period of time. This is natural and typical of this type of stone. Rust marks may also appear in the stone due to iron and mineral within the stone. This is not a fault and may be more visible when wet, and may become lighter in colour after installation, in dry conditions and over time.
- Sealing and treating:** All natural stone products can weather and develop algae and organic growth, and Sinai Pearl Limestone can be prone to freezethaw damage if not sealed. To help prevent this, preserve the colour and keep your investment in good condition, we highly recommend sealing Contempo Sinai Pearl Limestone. You can apply a sealant yourself or Kebur can pre-seal your stone for you with Dry-Treat Stain Proof™. This means it is ready to install in any weather and comes with a performance warranty.
- Installation:** We recommend that all natural stone is laid on a full mortar bed with a suitable sub-base, taking into account the ground conditions and planned usage. For Contempo Sinai Pearl we recommend substituting ordinary Portland cement with white cement. It should have an SBR bond slurry mix or similar applied to the underside of the slab to help with adhering to the mortar. Contempo Sinai Pearl Limestone should not be butt jointed. We recommend a minimum joint width of 5mm.
- There may be colour variations between batches of slabs. If laying from more than one pallet, mix slabs to ensure a consistent look.
- Maintenance:** We offer a range of sealers and cleaners you can use yourself. Never use acid based products for cleaning Contempo Sinai Pearl Limestone. Always read the label and seek professional guidance.

If you have any further questions about installing or caring for Contempo Sinai Pearl Limestone please contact one of our sales advisors who will be very happy to help you.