



Product guide: Contempo Brazilian Slate

Appearance: In all natural stone there will be variations in colour tones, shades and natural markings and they can display blemishes, veining and minor chips. This material may also be prone to superficial surface scratches which will weather over time. These are natural characteristics and enhance the uniqueness of the product. We always recommend viewing the product before making a decision. You can do this at our indoor and outdoor show areas. We can supply full size samples for an additional cost to help give an impression of how your finished project will look. We regret that we cannot refund or exchange products, once they have been installed, on the basis of texture, colour variation or other natural occurring characteristics.

Installation: We recommend that all natural stone is laid on a full mortar bed with a suitable sub-base, taking into account the ground conditions and planned usage. Contempo Brazilian Slate should have an SBR bond slurry mix or similar applied to the underside of the slab to help with adhering to the mortar.

Contempo Brazilian Slate should not be butt jointed. We recommend a minimum joint width of 5mm.

There may be colour variations between batches of slabs. If laying from more than one pallet, mix slabs to ensure a consistent look.

Maintenance: We offer a range of sealers and cleaners you can use yourself. Always read the label and seek professional guidance.

If you have any further questions about installing or caring for Contempo Brazilian Slate please contact one of our sales advisors who will be very happy to help you.



The Association of
**Professional
Landscapers**

Lynchford Lane, Farnborough, Hants, GU14 6JD
01252 517571 - sales@kebur.co.uk - www.kebur.co.uk

